

7-904

1753

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application Of: Thomason, Howard
Application No.: 09/898,606
Filed: July 3, 2001
Examiner: Kishor Mayekar
Art Unit: 1753
For: METHODS OF PREPARING AND USING ELECTROSTATICALLY TREATED FLUIDS

RESPONSE TO RESTRICTION REQUIREMENT

Sir:

This paper is submitted in response to the Notice of Non-Compliant Amendment and in further response to the March 12, 2004 requirement to elect between:

Claims 26-29 drawn to an energized fluid; and

Claims 30-41 drawn to a method of treating a fluid.

The following list reflects the current status of all pending claims:

1. (cancelled)
2. (cancelled)
3. (cancelled)
4. (cancelled)
5. (cancelled)
6. (cancelled)
7. (cancelled)
8. (cancelled)
9. (cancelled)
10. (cancelled)
11. (cancelled)

12. (cancelled)

13. (cancelled)

14. (cancelled)

15. (cancelled)

16. (cancelled)

17. (cancelled)

18. (cancelled)

19. (cancelled)

20. (cancelled)

21. (cancelled)

22. (cancelled)

23. (cancelled)

24. (cancelled)

25. (cancelled)

26. (cancelled)

27. (cancelled)

28. (cancelled)

29. (cancelled)

30. (Previously added) A method of increasing milk production in dairy cattle comprising the steps of:
- treating a water-containing source fluid with the an electrostatic device according to form an energized fluid; and

administering to dairy cattle an effective amount of the energized fluid for a period of time sufficient to increase milk production in the dairy cattle by at least 5% by volume with respect to milk production achieved by administering the source fluid to the dairy cattle;

wherein the electrostatic device comprises:

a fluid conduit;

a voltage spike signal generator for generating at least one voltage spike signal;

at least first and second radio frequency Rf signal generators for generating at least two different Rf signals having controlled frequencies; and

at least one antenna disposed in the fluid conduit for generating at least two different RF signals having controlled frequencies;

wherein:

the at least one antenna emits into a source fluid in the fluid conduit a combination signal comprising the at least one voltage spike signal and the at least two different Rf signals to form an energized fluid which can provide a measurable benefit to at least one of a living organism machinery, equipment, process and substance.

31. (Previously added) A method of increasing the octane rating in gasoline comprising the steps of treating a source gasoline with an electrostatic device for a period of time sufficient to form an energized gasoline having a final octane rating that is at least 5% greater than the octane rating of the source gasoline and wherein the electrostatic device comprises:

a fluid conduit;

a voltage spike signal generator for generating at least one voltage spike signal;

at least first and second radio frequency Rf signal generators for generating at least two different Rf signals having controlled frequencies; and

at least one antenna disposed in the fluid conduit for generating at least two different Rf signals having controlled frequencies;

wherein:

the at least one antenna emits into a source fluid in the fluid conduit a combination signal comprising the at least one voltage spike signal and the at least two different Rf signals to form an energized fluid which can provide a measurable benefit to at least one of a living organism machinery, equipment, process and substance.

32. (Previously added) A method of preparing cement having a reduced drying time comprising the steps of:

treating a source water with an electrostatic device to form an energized water;
and

mixing the energized water with a mixture to form a wet mass of cement having a drying time that is at least 40% shorter than a corresponding mass of cement made with the source water;

wherein the electrostatic device comprises:

a fluid conduit;
a voltage spike signal generator for generating at least one voltage spike signal;

at least first and second radio frequency Rf signal generators for generating at least two different Rf signals having controlled frequencies; and

at least one antenna disposed in the fluid conduit for generating at least two different RF signals having controlled frequencies;

wherein:

the at least one antenna emits into a source fluid in the fluid conduit a combination signal comprising the at least one voltage spike signal and the at least two different Rf signals to form an energized fluid which can provide a measurable benefit to at least one of a living organism machinery, equipment, process and substance.

33. (Previously added) A method of increasing meat production in at least one of poultry, swine, and cattle comprising the step of:

treating a water-containing source fluid with an electrostatic device to form an energized fluid; and

administering to the at least one of poultry, swine, and cattle an effective amount of the energized fluid for a period of time sufficient to provide at least one of poultry, swine and cattle having a meat mass which is greater than a meat mass of poultry, swine, and cattle, respectively, being administered the source fluid;

wherein the electrostatic device comprises:

a fluid conduit;

a voltage spike signal generator for generating at least one voltage spike signal;

at least first and second radio frequency Rf signal generators for generating at least two different Rf signals having controlled frequencies; and

at least one antenna disposed in the fluid conduit for generating at least two different RF signals having controlled frequencies;

wherein:

the at least one antenna emits into a source fluid in the fluid conduit a combination signal comprising the at least one voltage spike signal and the at least two different Rf signals to form an energized fluid which can provide a measurable benefit to at least one of a living organism machinery, equipment, process and substance.

34. (Previously added) A method of increasing a nutrition value of a feed grass comprising the steps of:

treating a water-containing source fluid with an electrostatic device to form an energized water-containing fluid; and

administering to the feed grass an effective amount of the energized water based fluid for a period of time sufficient to form an improved feed grass having a nutritional component present in a first amount which is greater than a corresponding second amount in the feed grass that has been treated with the water-containing source fluid;

wherein the electrostatic device comprises:

a fluid conduit;

a voltage spike signal generator for generating at least one voltage spike signal;

at least first and second radio frequency Rf signal generators for generating at least two different Rf signals having controlled frequencies; and

at least one antenna disposed in the fluid conduit for generating at least two different RF signals having controlled frequencies;

wherein:

the at least one antenna emits into a source fluid in the fluid conduit a combination signal comprising the at least one voltage spike signal and the at least two different Rf signals to form an energized fluid which can provide a measurable benefit to at least one of a living organism machinery, equipment, process and substance.

35. (Previously added) A method of Claim 34 wherein the feed grasses are selected from a group consisting of:

Rhodes grass, alfalfa, lawn grass, sod grass, barley, wheat, rye, Saint Augustine grass, tiff green grass, Bermuda grass, Clover grass, Johnson grass, San Love grass, bluegrass, blue stem grass, Gramma Green grass, buffalo grass, clover grass, prairie grass, hay, and dichondra grass.

36. (Previously added) A method of increasing crop production comprising the step of:

treating a water-containing source fluid with an electrostatic device to form an water-containing energized fluid; and

treating a crop with an effective amount of the energized fluid for a period of time sufficient to increase a production of the crop with respect to a corresponding production which would be obtained by treating the crop with the source fluid;

wherein the electrostatic device comprises:

a fluid conduit;

a voltage spike signal generator for generating at least one voltage spike signal;

at least first and second radio frequency Rf signal generators for generating at least two different Rf signals having controlled frequencies; and

at least one antenna disposed in the fluid conduit for generating at least two different RF signals having controlled frequencies;

wherein:

the at least one antenna emits into a source fluid in the fluid conduit a combination signal comprising the at least one voltage spike signal and the at least two different Rf signals to form an energized fluid which can provide a measurable benefit to at least one of a living organism machinery, equipment, process and substance.

37. (Previously added) The method of Claim 36 wherein the crop is selected from the group consisting of:

wheat, barley, tomatoes, peppers, cauliflower, broccoli, strawberries, lettuce, onion, cabbage, melons, grapes, dates, citrus fruits, potatoes, corn, peanuts, lettuce, squash, fruit tree crop, and fruit bush crop.

38. (Previously added) A method of producing an energized beverage having reduced beverage concentrate comprising the steps of:

treating a source water with an electrostatic device to form an energized water;

treating a source beverage concentrate with the electrostatic device to form an energized beverage concentrate; and

mixing the energized water and the energized beverage concentrate to form an energized beverage;

wherein the energized beverage requires less beverage concentrate to perform substantially the same as a corresponding unenergized beverage in a taste test; and

wherein the electrostatic device comprises:

a fluid conduit;

voltage spike signal generator for generating at least one voltage spike signal;

at least first and second radio frequency Rf signal generators for generating at least two different Rf signals having controlled frequencies; and

at least one antenna disposed in the fluid conduit for generating at least two different RF signals having controlled frequencies;

wherein:

the at least one antenna emits into a source fluid in the fluid conduit a combination signal comprising the at least one voltage spike signal and the at least two different Rf signals to form an energized fluid which can provide a measurable benefit to at least one of a living organism machinery, equipment, process and substance.

39. (Previously added) An improved method of combusting a fluid comprising the steps of:

treating a source fluid with an electrostatic device to form an energized fluid; and
combusting the energized fluid in a stack;

wherein combustion of the energized fluid results in at least one of a lower carbon dioxide emission level, a lower smoke emission level, a lower required stack temperature, and improved flame performance as compared to combustion of the source fluid in the stack; and

wherein the electrostatic device comprises:

a fluid conduit;

a voltage spike signal generator for generating at least one voltage spike signal;

at least first and second radio frequency Rf signal generators for generating at least two different Rf signals having controlled frequencies; and

at least one antenna disposed in the fluid conduit for generating at least two different RF signals having controlled frequencies;

wherein:

the at least one antenna emits into a source fluid in the fluid conduit a combination signal comprising the at least one voltage spike signal and the at least two different Rf signals to form an energized fluid which can provide a measurable benefit to at least one of a living organism machinery, equipment, process and substance.

40. (Previously added) A method of tracking a fluid flowing through a fluid conduit comprising the steps of:

treating a fluid flowing through a first point of a fluid conduit with an electrostatic device to energize the fluid; and

monitoring a property of the fluid at a downstream second point of the fluid conduit to determine whether the fluid has been energized;

wherein a change in the property corresponds substantially with a change in energy of the fluid; and

wherein the electrostatic device comprises:

a fluid conduit;

a voltage spike signal generator for generating at least one voltage spike signal;

at least first and second radio frequency Rf signal generators for generating at least two different Rf signals having controlled frequencies; and

at least one antenna disposed in the fluid conduit for generating at least two different RF signals having controlled frequencies;

wherein:

the at least one antenna emits into a source fluid in the fluid conduit a combination signal comprising the at least one voltage spike signal and the at least two different Rf signals to form an energized fluid which can provide a measurable benefit to at least one of a living organism machinery, equipment, process and substance.

41. (Previously added) An improved method of producing shrimp comprising the steps of:

treating a salt water source with an electrostatic device to form energized salt water; and

treating a first group of shrimp with an effective amount of the energized salt water for a period of time sufficient to at least one of increase the production of, increase the survival rate of, reduce the feed requirement of and reduce the time-to-market of the first group

of shrimp as compared to a substantially similar second group of shrimp not treated with the energized salt water;

wherein the electrostatic device comprises:

a fluid conduit;

a voltage spike signal generator for generating at least one voltage spike signal;

at least first and second radio frequency Rf signal generators for generating at least two different Rf signals having controlled frequencies; and

at least one antenna disposed in the fluid conduit for generating at least two different RF signals having controlled frequencies;

wherein:

the at least one antenna emits into a source fluid in the fluid conduit a combination signal comprising the at least one voltage spike signal and the at least two different Rf signals to form an energized fluid which can provide a measurable benefit to at least one of a living organism machinery, equipment, process and substance.

The Commissioner is authorized to charge any additional fees required to Deposit
Account 19-4547.


Cordially,

A handwritten signature in black ink, appearing to read "Alan R. Thiele", written in a cursive style.

Alan R. Thiele
Registration No. 30,694

Date: July 8, 2004

Strasburger & Price, LLP
901 Main Street, Suite 4300
Dallas, TX 75202-3794
Telephone: (214) 651-4300, ext. 6014
Facsimile: (214) 651-4330
alan.thiele@strasburger.com



PTO/SB/21 (02-04)

Approved for use through 07/31/2006. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

TRANSMITTAL FORM (to be used for all correspondence after initial filing)	Application Number	09/898,606	
	Filing Date	July 3, 2001	
	First Named Inventor	Thomason, Howard	
	Art Unit	1753	
	Examiner Name	Kishor Mayekar	
Total Number of Pages in This Submission	14	Attorney Docket Number	24171.0111

ENCLOSURES (Check all that apply)		
<input type="checkbox"/> Fee Transmittal Form <input type="checkbox"/> Fee Attached <input checked="" type="checkbox"/> Amendment/Reply <input type="checkbox"/> After Final <input type="checkbox"/> Affidavits/declaration(s) <input type="checkbox"/> Extension of Time Request <input type="checkbox"/> Express Abandonment Request <input type="checkbox"/> Information Disclosure Statement <input type="checkbox"/> Certified Copy of Priority Document(s) <input type="checkbox"/> Response to Missing Parts/Incomplete Application <input type="checkbox"/> Response to Missing Parts under 37 CFR 1.52 or 1.53	<input type="checkbox"/> Drawing(s) <input type="checkbox"/> Licensing-related Papers <input type="checkbox"/> Petition <input type="checkbox"/> Petition to Convert to a Provisional Application <input type="checkbox"/> Power of Attorney, Revocation <input type="checkbox"/> Change of Correspondence Address <input type="checkbox"/> Terminal Disclaimer <input type="checkbox"/> Request for Refund <input type="checkbox"/> CD, Number of CD(s) _____	<input type="checkbox"/> After Allowance communication to Technology Center (TC) <input type="checkbox"/> Appeal Communication to Board of Appeals and Interferences <input type="checkbox"/> Appeal Communication to TC (Appeal Notice, Brief, Reply Brief) <input type="checkbox"/> Proprietary Information <input type="checkbox"/> Status Letter <input checked="" type="checkbox"/> Other Enclosure(s) (please identify below):
Remarks Postcard acknowledgment		
SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT		
Firm or Individual name	Alan R. Thiele Strasburger & Price, LLP	
Signature		
Date	7/8/04	

CERTIFICATE OF TRANSMISSION/MAILING		
I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first-class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below. <div style="text-align: center;">for U.S. Express Mail (No. EL-650191613-US)</div>		
Typed or printed name	Maria Reyna	
Signature		Date 7/8/04

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.